



1	VDD	
2	VSS	Ground
3	NC	No connection
4	/CS	Chip select
5	A0	
6	/RD	
7	/WR	Write signal
8	/RES	Reset signal
9	DB0	
10	DB1	DATA 1
11	DB2	DATA BUS 2
12	DB3	DATA BUS 3
13	DB4	DATA BUS 4
14	DB5	DATA BUS 5
15	DB6	DATA BUS 6
16	DB7	DATA BUS 7
17	A	Backlight (+) +3.3V
18	K	Backlight (-)

NOTES:

1. DISPLAY TYPE: STN,BLUE
2. POLARIZER TYPE: TRANSMISSIVE,NEGATIVE
3. VIEW DIRECTION: 6:00
4. OPERATING TEMPERATURE: -20°C~+70°C
5. STORAGE TEMPERATURE: -30°C~+80°C
6. VDD: +3.3V
7. DRIVE METHOD: 1/128DUTY,1/12BIAS
8. CONTROLLER: UC1698
9. BACKLIGHT TYPE: WHITE,SIDE
10. BACKLIGHT SUPPLY VOLTAGE: +3.3V

Autodesk 教育版产品制作



WAYING (HONGKONG) SHARES LIMITED

DESIGN:

MODEL NUMBER: WYM240128K4

CHECK:

VERSION: A

APPROVE:

SHEET: 1 OF 1

Unspecified tolerances are ±0.3

DATE: 2013-03-15